

MATERIAL SAFETY DATA SHEET

Environmental Lubricants Manufacturing, Inc.
1307 Badger Avenue
Plainfield, IA 50666

ELM Bar & Chain Lubricant

HMIS: Health - 0, Fire - 1, Reactivity - 0

Date Issued: 04/27/99

Emergency Phone Number: **(319) 276-4801**

Date Revised: 05/31/05

24 Hour Emergency Assistance - CHEMTREC: (800) 424-9300

I. IDENTIFICATION & PHYSICAL DATA

Product Name: Bar & Chain Lubricant

Percent Volatile by Volume: 0%

Product Class: Formulated Lubricating Oil

Boiling Range: ND

Manufacturer's I.D. Bar & Chain Lubricant

Vapor Density: Heavier Than Air

VOC: ND

Specific Gravity: ND

Solubility In Water: Practically Insoluble

Vapor Pressure at 20 C: <0.5 mm Hg

Evaporation Rate: Slower Than Butyl Acetate

Specific Gravity (H₂O=1.0): 0.915

Appearance and Odor: Amber liquid with faint vegetable oil odor

Weight per Gallon: 7.64 lbs. at 60 °F

II. COMPOSITION/INFORMATION ON INGREDIENTS

	CAS #	OSHA TWA	OSHA STEL	ACGIH TWA	ACGIH STEL
Soybean Oil	8001-22-7	---	10 mg/m ³	---	---
Additive Mixture*	Confidential	---	---	---	10 mg/m ³

*The specific chemical identity is being withheld as a trade secret.

--- Not established

THE PRECISE COMPOSITION OF THIS PRODUCT IS PROPRIETARY INFORMATION. A MORE COMPLETE DISCLOSURE WILL BE PROVIDED TO A PHYSICIAN IN THE EVENT OF A MEDICAL EMERGENCY.

SARA HAZARD: NONE NOTED (SECNON 311/312) TITLE III SECTION 313 - NOT LISTED

All components of this product are listed on the TSCA registry.

III. FIRE & EXPLOSION DATA

Flash Point: 284°C/544°F

Fire Point: 314°C/597°F

LEL: No Data

Extinguishing Media:

Use carbon dioxide or dry chemical.

Unusual Fire & Explosion Hazards:

Closed containers may rupture (due to buildup of pressure) when exposed to extreme heat.

Special Fire Fighting Procedures:

Wear self-contained breathing apparatus and complete personal protective equipment when entering confined areas where potential for exposure to vapors or products of combustion exists.

IV. REACTIVITY DATA

Stability: Stable

Hazardous Polymerization:

Will not occur

Conditions to Avoid:

Fire, excessive heat.

Materials to Avoid:

Strong oxidizing agents.

Hazardous Decomposition Products:

Fumes produced when heated to decomposition may include: carbon monoxide, carbon dioxide.

V. HEALTH HAZARD DATA

Effects of Overexposure:

Ingestion: No specific information available.

Contains materials that may be practically non-toxic.

Inhalation: No specific information available.

Heating can generate vapors that could cause headaches, nausea, dizziness, and respiratory irritation if inhaled.

Skin Absorption: No specific information available.

Contains materials that may be practically non-toxic.

Skin Contact: No specific information available.

Contains materials that may cause skin irritation on prolonged or repeated exposure.

Eye Contact: No specific information available.

Contains materials that may cause eye injury, which may persist for several days.

Chronic Effects of Overexposure: No information available.

Emergency & First Aid Procedures:

Eye Contact:

Flush with plenty of water for at least 15 minutes and seek medical attention if irritation persists.

Skin Contact:

Remove contaminated clothing and wash contact area with soap and water for 15 minutes.

Ingestion:

If appreciable quantities are swallowed, seek medical attention.

Inhalation:

In case of over exposure to fumes if product is heated, remove person to fresh air. If breathing has stopped, administer artificial respiration and seek medical attention.

VI. SPILL OR LEAK PROCEDURES

Steps to Be Taken In Case Material Is Released or Spilled:

Scoop up and collect for disposal. Absorb any remaining residue with inert material and dispose. Flush area with water.

Spills or releases to the environment may be reportable to the National Response Center (800-424-8802) and to state and/or local agencies.

Waste Disposal Method:

Incinerate or use biological treatment in accordance with federal, state, and local regulations.

VII. SPECIAL PROTECTION INFORMATION

Respiratory Protection:

Wear a properly fitted NIOSH/MSHA approved respirator whenever exposure to vapor from heating product is likely and where ventilation is inadequate.

Ventilation:

Local Exhaust: Recommended when appropriate to control employee exposure.

Mechanical: Not recommended as the sole means of controlling employee exposure.

Protective Gloves: For operations where contact can occur, wear impervious gloves.

Eye Protection: Safety goggles.

Other Protective Equipment: For operations where contact can occur, a safety shower and eye wash facility should be available.

VIII. SPECIAL PRECAUTIONS

Store it in a dry place. Keep container closed. Avoid breathing mist and fumes when heating during use.

IX. STATE R-T-K COMPOSITION INFORMATION (and Canada)

Component	CAS #	DSL	NDSL
Soybean Oil	8001-22-7	Yes	No
Additive Mixture**	Confidential	---	---

**The specific chemical identity is being withheld by suppliers as a trade secret.

X. SARA Title III, Section 313 Information:

This product does not contain any SARA Title III Section 313 chemicals.

XI. RCRA Information

Regulated Waste: No

XII. CERCLA INFORMATION

Under EPA-CERCLA releases to air, land, or water which exceed the reportable quantity must be reported to the National Response Center (800-424-8802).

This product contains no materials with reportable quantities.

XIII. California Proposition 65 Information:

To the best of our knowledge, this product does not contain any California Proposition 65 designated chemicals.

XIV. Transportation Information

D.O.T. Shipping Name: Not Regulated

D.O.T. Hazard Class: Not Regulated

D.O.T. UN/NA Number: None

XV. Other Information

None.

To the best knowledge of Environmental Lubricants Manufacturing, Inc. (ELM), the information contained herein is accurate and reliable as of the date of this material safety data sheet. However no liability whatsoever is assumed for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown health hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.