

ELM Drill Rod Grease NLGI Grade 1, 2 & 3
Part Number: G-100, G-110, G-120
Biodegradable Drilling Lubricant



DESCRIPTION ELM Drill Rod Grease is a premium quality biodegradable, Biotechbased™ Drilling Lubricant formulated from USA-grown vegetable oils and a aluminum complex based thickener.

BIOBASED-BIODEGRADABLE-NON-BIOACCUMULATIVE Based on evaluation of the base oils and the finished products, the ELM biobased products are designed to be biodegradable, aquatically non-toxic, not-bioaccumulative, and with no impact on plants as determined by known test methods. Nevertheless, the use of all of ELM products are subject to the local ordinances and ultimate responsibility for impact remains with the users.

- APPLICATIONS**
- Designed for applications with high temperature requirements
 - Recommended for heavy load applications
 - Recommended for environmentally sensitive areas near waterways

- BENEFITS**
- Contains advanced extreme pressure additives
 - Reduces friction and wear
 - Formulated to be applied on wet surfaces
 - Better coefficient of friction than most petroleum-based grease
 - Improves efficiency and superior lubricity
 - Higher flash point than major petroleum greases for increased safety
 - Biodegradable formula reduces damage to the environment
 - Meets EPA's Environmental Preferable Purchasing (EPP) criteria
 - Meets USDA's proposed Biobased product definition for EO 13101
 - Manufactured from renewable USA-grown crop-based oils

| TYPICAL PROPERTIES | <u>Grade 1</u> | <u>Grade 2</u> | <u>Grade 3</u> |
|--------------------------------------|----------------|----------------|----------------|
| Appearance | Golden-Brown | Golden-Brown | Golden-Brown |
| Cone Penetration, Unworked | 310-340 | 265-295 | 220-250 |
| Four Ball Wear Scar (mm) | >0.55 | >0.5 | >0.45 |
| Four Ball Weld Load (kg) | >400 | >500 | >500 |
| Dropping Point °C (°F) | >240°C | >240°C | >240°C |
| Oil Separation | <7% | <5% | <5% |
| Base Oil Viscosity at 40°C (cSt) | 180 | 220 | 460 |
| Base Oil Viscosity at 100°C (cSt) | 22 | 36 | 58 |
| Base Oil Viscosity Index | 198 | 214 | 196 |
| Base Oil Flash Point, °C (°F) | 326 (619) | 326 (619) | 326 (619) |
| Base Oil Biodegradability – OECD 301 | Pass | Pass | Pass |
| Base Oil Aquatic Toxicity – OECD 202 | Non-toxic | Non-toxic | Non-toxic |
| Base Oil Plant Toxicity - OECD 208 | Non-toxic | Non-toxic | Non-toxic |

PACKAGING

35 lb. Pails
 400 lb. Drums
 2100 lb Totes

DATA PROVIDED IN THIS BULLETIN IS TO BE CONSIDERED AS REPRESENTATIVE OF CURRENT PRODUCTION GENERALLY AND NOT AS SPECIFICATIONS. WHILE ALL THE DATA PRESENTED IN THIS BULLETIN IS BELIEVED TO BE RELIABLE, AND BECAUSE CONDITIONS OF USE ARE BEYOND OUR CONTROL, ELM MAKES NO REPRESENTATIONS, GUARANTEES OR WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING BUT NOT LIMITED TO ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE, OR AS TO THE CORRECTNESS OR SUFFICIENCY OF DATA HEREIN PRESENTED. EACH USER SHOULD CONDUCT A SUFFICIENT INVESTIGATION TO ESTABLISH THE FITNESS OF ANY PRODUCT FOR ITS INTENDED PURPOSE. NO AGENT, REPRESENTATIVE, OR EMPLOYEE OF THIS COMPANY IS AUTHORIZED TO VARY ANY OF THE TERMS OF THIS NOTICE. TO CONTINUE TO PROVIDE SUPERIOR QUALITY, ELM RESERVES THE RIGHT TO CHANGE THE COMPOSITION OF ITS PRODUCTS WITHOUT NOTICE.

Biotechbased™ and the ELM logo are trademarks of Environmental Lubricants Manufacturing, Inc. **Last updated 04-15-2019**