## ELM Semi-Truck Fifth Wheel Grease NLGI Grade #2



Part Number: G-220

**BENEFITS** 

**Biodegradable Lithium Grease** 

DESCRIPTION	Fifth Wheel Grease is premium quality biodegradable, Biotech based™ multipurpose
	grease formulated from USA-grown vegetable oils and a lithium-based thickener.

Based on evaluation of the base oils and the finished products, the ELM biobased **BIOBASED-BIODEGRADABLE-**NON-BIOACCUMULATIVE

products are designed to be biodegradable, aquatically non-toxic, notbioaccumulative, and with no impact on plants as determined by known test methods. Nevertheless, the use of all of ELM products are subject to the local ordinances and ultimate responsibility for impact remains with the users.

APPLICATIONS	Recommended for use on semi truck fifth wheel plates
	Perfect for trailer hitches or other mechanical joints

Great protection from metal sliding contact

Provides superior lubricity to promote longer equipment life Lithium based thickener resists thinning at high temperatures

Superior adhesion and resists water washout Protects ferrous metals from rust and corrosion Mostly benign when released into the environment

Contains advanced extreme pressure additives for excellent protection Higher flash point than petroleum greases for increased safety Biodegradable formula reduces damage to the environment Meets EPA's Environmental Preferable Purchasing (EPP) criteria

PERFORMANCE	
LEVELS	Meets most manufacturer's specifications

	Appearance	Red
	NLGI Grade	2
TYPICAL PROPERTIES	Cone Penetration, Worked (60x)	265-295
	Four Ball Wear Scar (mm)	0.52
	Four Ball Weld Load (kg)	400
	Dropping Point °C (°F)	170 (338)
	Oil Separation	<5%
	Base Oil Viscosity at 40°C (cSt)	220
	Base Oil Viscosity at 100°C (cSt)	36

Base Oil Viscosity Index

Base Oil Flash Point, °C (°F) 326 (619) Base Oil Biodegradability - OECD 301 Pass Base Oil Aquatic Toxicity - OECD 202 Non-toxic Base Oil Plant Toxicity - OECD 208 Non-toxic

214

14 oz Cartridges **PACKAGING** 35-lb Pails and 120 lb Kegs 2100 lb Totes

DATA PROVIDED IN THIS BULLETIN IS TO BE CONSIDERED AS REPRESENTATIVE OF CURRENT PRODUCTION GENERALLY AND NOT AS SPECIFICATIONS. WHILE ALL THE DATA PRESENTED IN THIS BULLETIN IS BELIEVED TO BE RELIABLE, AND BECAUSE CONDITIONS OF USE ARE BEYOND OUR CONTROL, ELM MAKES NO REPRESENTATIONS, GUARANTEES OR WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING BUT NOT LIMITED TO ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE, OR AS TO THE CORRECTNESS OR SUFFICIENCY OF DATA HEREIN PRESENTED. EACH USER SHOULD CONDUCT A SUFFICIENT INVESTIGATION TO ESTABLISH THE FITNESS OF ANY PRODUCT FOR ITS INTENDED PURPOSE. NO AGENT, REPRESENTATIVE, OR EMPLOYEE OF THIS COMPANY IS AUTHORIZED TO VARY ANY OF THE TERMS OF THIS NOTICE. TO CONTINUE TO PROVIDE SUPERIOR QUALITY, ELM RESERVES THE RIGHT TO CHANGE THE COMPOSITION OF ITS PRODUCTS WITHOUT NOTICE.