

ELM 85W-140 Gear Lubricant
Part Number: ILO-120
Biodegradable – Biobased Gear Lubricant



DESCRIPTION	ELM 85W140 Multi-Purpose Gear Lubricant is a premium quality biodegradable gear lubricant formulated with the best optimized Biotechbased™ USA-grown natural seed oil that surpasses the lubricity of most conventional oils. It protects against wear, has a high flash point for safety and is readily biodegradable.	
BIOBASED – BIODEGRADABLE-NON- BIOACCUMULATIVE	Based on evaluation of the base oils and the finished products, the ELM biobased products are designed to be biodegradable, aquatically non-toxic, not-bioaccumulative, and with no impact on plants as determined by known test methods. Nevertheless, the use of all of ELM products are subject to the local ordinances and ultimate responsibility for impact remains with the users.	
APPLICATIONS	<ul style="list-style-type: none"> ■ Specifically formulated to meet the demanding applications of gears and drives where heavy loads and high torque are present ■ Suited for use where an API GL-5 performance level is specified ■ For use where industrial gear oils are specified 	
BENEFITS	<ul style="list-style-type: none"> ■ Superior lubricity protects gears from wear ■ Protects ferrous metal components from rust and corrosion ■ Designed to handle both sliding and rolling loads ■ Reduces vibration and noise ■ Mostly benign when released into the environment ■ Meets USDA's proposed biobased product definition for EO 13101 ■ Meets EPA's Environmental Preferable Purchasing (EPP) criteria ■ Made from renewable USA-grown crop-based oils ■ Meets State of Iowa Senate File 2249 Purchasing Preference for Biobased Lubricants 	
PERFORMANCE LEVELS	<ul style="list-style-type: none"> ■ Designed to provide the wear performance requirements of API GL-5 	
TYPICAL PROPERTIES	SAE Viscosity Grade	85W-140
	Viscosity at 40°C	320-330
	Viscosity at 100°C (cSt)	38-39
	Viscosity Index	170-174
	Flash Point, °C (°F)	209 (408)
	Low Temperature, °C	< -20
	Four Ball Wear (ASTM D 4172, Scar Diameter)	0.39 mm
	Weld Load (ASTM D 2596)	500 kg
	Base Oil Biodegradability – OECD 301	Pass
	Base Oil Aquatic Toxicity – OECD 202	Non-toxic
	Base Oil Plant Toxicity - OECD 208	Non-toxic
PACKAGING	5 Gal. Pails 55 Gal. Drums 275 Gal. Totes	

DATA PROVIDED IN THIS BULLETIN IS TO BE CONSIDERED AS REPRESENTATIVE OF CURRENT PRODUCTION GENERALLY AND NOT AS SPECIFICATIONS. WHILE ALL THE DATA PRESENTED IN THIS BULLETIN IS BELIEVED TO BE RELIABLE, AND BECAUSE CONDITIONS OF USE ARE BEYOND OUR CONTROL, ELM MAKES NO REPRESENTATIONS, GUARANTEES OR WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING BUT NOT LIMITED TO ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE, OR AS TO THE CORRECTNESS OR SUFFICIENCY OF DATA HEREIN PRESENTED. EACH USER SHOULD CONDUCT A SUFFICIENT INVESTIGATION TO ESTABLISH THE FITNESS OF ANY PRODUCT FOR ITS INTENDED PURPOSE. NO AGENT, REPRESENTATIVE, OR EMPLOYEE OF THIS COMPANY IS AUTHORIZED TO VARY ANY OF THE TERMS OF THIS NOTICE. TO CONTINUE TO PROVIDE SUPERIOR QUALITY, ELM RESERVES THE RIGHT TO CHANGE THE COMPOSITION OF ITS PRODUCTS WITHOUT NOTICE.